

ZINC NON-WATERTIGHT SHORT BODY CONNECTORS

FOR NON-METALLIC SHEATHED CABLE AND SERVICE ENTRANCE CABLE

APPLICATION:

- Used with locknut to terminate service entrance cable to enclosure.

FEATURES:

- Assembled with die cast locknut and tri-combo screws.
- For round cable.

STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES


UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated


TYPE C50S

CATALOG NUMBER	TRADE SIZE	DIM A MIN.	DIM A MAX.	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
C50S	1"	0.620	1.140	1.500	10	100	15	64601
C51S	1-1/4"	0.700	1.380	1.900	10	100	24	64602
C52S	1-1/2"	0.750	1.610	2.115	10	100	34	64603
C53S	2"	0.900	2.040	2.640	5	50	46	64604

Please see Cable Chart for Cable Connectors on Page 194.


TYPE C50ST
Insulated

CATALOG NUMBER	TRADE SIZE	DIM A MIN.	DIM A MAX.	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
C50ST	1"	0.620	1.140	1.500	10	100	15	90138
C51ST	1-1/4"	0.700	1.380	1.900	10	100	24	90139
C52ST	1-1/2"	0.750	1.610	2.115	10	100	34	90140
C53ST	2"	0.900	2.040	2.640	5	50	46	90141

Please see Cable Chart for Cable Connectors on Page 194.

CATALOG NUMBER	SE/oval diameter in.	Ser/round diameter in.
C50S and C50ST Non-Metallic Cable 10-3 through 4-3	(.51 by .80) and (.62 by .975)	(.69) and (.92)
C51S and C51ST Non-Metallic Cable 4-3 through 2-3	(.67 by 1.06) and (.73 by 1.235)	1.19
C52S and C52ST	(1.15 by 0.73) and (1.41 by 0.89)	1.48
C53S and C53ST	(1.405 by 0.875) and (1.450 by 0.875)	—