




# MALLEABLE IRON 3-PIECE COUPLINGS

## FOR THREADED RIGID CONDUIT AND IMC



### APPLICATION:

- Used to join two lengths of threaded conduit.

### FEATURES:

- Threaded (NPS) for rigid conduit and IMC.
- Concrete tight.

### STANDARD MATERIALS:

Malleable Iron

### STANDARD FINISH:

Zinc Plated

### CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258  
UL Standard: UL514B  
NEMA FB-1  
ASTM Rated




## TYPE 1023

| CATALOG NUMBER | TRADE SIZE | DIM A | DIM B | DIM C | UNIT PACK | MASTER PACK | LBS./100 PCS | UPC # |
|----------------|------------|-------|-------|-------|-----------|-------------|--------------|-------|
| 1022           | 1/2"       | 1.38  | 1.36  | 1.36  | 20        | 200         | 26           | 10221 |
| 1023           | 3/4"       | 1.63  | 1.58  | 1.58  | 10        | 100         | 37           | 10231 |
| 1024           | 1"         | 1.81  | 1.89  | 1.89  | —         | 20          | 55           | 10241 |
| 1025           | 1-1/4"     | 2.19  | 2.38  | 2.38  | —         | 20          | 111          | 10251 |
| 1026           | 1-1/2"     | 2.31  | 2.83  | 2.83  | —         | 10          | 172          | 10261 |
| 1027           | 2"         | 2.44  | 3.29  | 3.29  | —         | 10          | 203          | 10271 |
| 1028           | 2-1/2"     | 3.19  | 4.08  | 4.08  | 2         | 10          | 327          | 10281 |
| 1029           | 3"         | 3.31  | 4.67  | 4.67  | 2         | 10          | 442          | 10291 |
| 1030           | 3-1/2"     | 3.50  | 5.07  | 5.07  | 1         | 5           | 608          | 10301 |
| 1031           | 4"         | 3.75  | 5.75  | 5.75  | 1         | 5           | 718          | 10311 |
| 1005           | 5"         | 3.69  | 6.88  | 7.50  | —         | 1           | 1050         | 10051 |
| 1006           | 6"         | 4.31  | 8.00  | 8.00  | —         | 1           | 1250         | 10061 |

# MALLEABLE IRON/HOT DIPPED GALVANIZED

## 3-PIECE COUPLINGS

## FOR THREADED RIGID CONDUIT AND IMC



### APPLICATION:

- Used to join two lengths of threaded conduit.

### FEATURES:

- Threaded (NPS) for rigid conduit and IMC.
- Concrete tight.

### STANDARD MATERIALS:

Malleable Iron

### STANDARD FINISH:

Hot Dipped Galvanized/Zinc Plated



### CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258  
UL Standard: UL514B  
NEMA FB-1  
ASTM Rated

## TYPE 1023G

| CATALOG NUMBER | TRADE SIZE | DIM A | DIM B | DIM C | UNIT PACK | MASTER PACK | LBS./100 PCS | UPC # |
|----------------|------------|-------|-------|-------|-----------|-------------|--------------|-------|
| 1022G          | 1/2"       | 1.38  | 1.36  | 1.36  | 20        | 200         | 26           | 10009 |
| 1023G          | 3/4"       | 1.63  | 1.58  | 1.58  | 10        | 100         | 37           | 10210 |
| 1024G          | 1"         | 1.81  | 1.89  | 1.89  | —         | 20          | 55           | 10011 |
| 1025G          | 1-1/4"     | 2.19  | 2.38  | 2.38  | —         | 20          | 111          | 10012 |
| 1026G          | 1-1/2"     | 2.31  | 2.83  | 2.83  | —         | 10          | 172          | 10013 |
| 1027G          | 2"         | 2.44  | 3.29  | 3.29  | —         | 10          | 203          | 10014 |
| 1028G          | 2-1/2"     | 3.19  | 4.08  | 4.08  | 2         | 10          | 327          | 10015 |
| 1029G          | 3"         | 3.31  | 4.67  | 4.67  | 2         | 10          | 442          | 10016 |
| 1030G          | 3-1/2"     | 3.50  | 5.07  | 5.07  | 1         | 5           | 608          | 10017 |
| 1031G          | 4"         | 3.75  | 5.75  | 5.75  | 1         | 5           | 718          | 10018 |
| 1005G          | 5"         | 3.69  | 6.88  | 7.50  | —         | 1           | 1050         | 10019 |
| 1006G          | 6"         | 4.31  | 8.00  | 8.00  | —         | 1           | 1250         | 10020 |

