

# MALLEABLE IRON RIGID SET-SCREW CONNECTORS

## FOR THREADLESS RIGID CONDUIT AND IMC

### APPLICATION:

- To connect threadless rigid conduit to boxes and enclosures.

### FEATURES:

- Concrete tight.
- Available with insulated throat.
- Male hub thread (NPS).

### STANDARD MATERIALS:

Malleable Iron


### STANDARD FINISH:

Zinc Plated

### CERTIFICATIONS AND COMPLIANCES




**UL LISTED E198258**  
UL Standard: UL514B  
NEMA FB-1  
ASTM Rated



## TYPE TRC-50

| CATALOG NUMBER | TRADE SIZE | DIM A | DIM B | DIM C | UNIT PACK | MASTER PACK | LBS./100 PCS | UPC # |
|----------------|------------|-------|-------|-------|-----------|-------------|--------------|-------|
| TRC-50         | 1/2"       | 1.375 | 0.438 | 1.313 | 25        | 250         | 13           | 70830 |
| TRC-75         | 3/4"       | 1.688 | 0.500 | 1.563 | 25        | 100         | 21           | 70831 |
| TRC-100        | 1"         | 1.938 | 0.563 | 1.875 | 5         | 25          | 38           | 70832 |
| TRC-125        | 1-1/4"     | 2.188 | 0.625 | 2.188 | 5         | 25          | 44           | 70833 |
| TRC-150        | 1-1/2"     | 2.313 | 0.625 | 2.500 | 5         | 20          | 67           | 70834 |
| TRC-200        | 2"         | 2.438 | 0.625 | 2.938 | 2         | 10          | 105          | 70835 |
| TRC-250        | 2-1/2"     | 3.188 | 0.750 | 3.625 | 2         | 10          | 190          | 70836 |
| TRC-300        | 3"         | 3.813 | 0.875 | 4.250 | 1         | 5           | 272          | 70837 |
| TRC-350        | 3-1/2"     | 4.313 | 0.938 | 4.688 | 1         | 5           | 367          | 70838 |
| TRC-400        | 4"         | 4.625 | 0.938 | 5.188 | 1         | 5           | 427          | 70839 |
| TRC-500        | 5"         | 4.750 | 1.375 | 6.500 | —         | 1           | 695          | 70890 |
| TRC-600        | 6"         | 4.938 | 1.500 | 7.500 | —         | 1           | 911          | 70900 |



## TYPE TRC-50T

**Insulated Throat**

| CATALOG NUMBER | TRADE SIZE | DIM A | DIM B | DIM C | UNIT PACK | MASTER PACK | LBS./100 PCS | UPC # |
|----------------|------------|-------|-------|-------|-----------|-------------|--------------|-------|
| TRC-50T        | 1/2"       | 1.375 | 0.500 | 1.313 | 25        | 250         | 14           | 70840 |
| TRC-75T        | 3/4"       | 1.688 | 0.563 | 1.563 | 25        | 100         | 22           | 70841 |
| TRC-100T       | 1"         | 1.938 | 0.625 | 1.875 | 5         | 25          | 39           | 70842 |
| TRC-125T       | 1-1/4"     | 2.188 | 0.688 | 2.188 | 5         | 25          | 54           | 70843 |
| TRC-150T       | 1-1/2"     | 2.313 | 0.688 | 2.500 | 5         | 20          | 70           | 70844 |
| TRC-200T       | 2"         | 2.438 | 0.688 | 2.938 | 2         | 10          | 106          | 70845 |
| TRC-250T       | 2-1/2"     | 3.188 | 0.813 | 3.625 | 2         | 10          | 191          | 70846 |
| TRC-300T       | 3"         | 3.813 | 0.938 | 4.250 | 1         | 5           | 280          | 70847 |
| TRC-350T       | 3-1/2"     | 4.313 | 1.000 | 4.688 | 1         | 5           | 380          | 70848 |
| TRC-400T       | 4"         | 4.500 | 1.000 | 5.188 | 1         | 5           | 455          | 70849 |
| TRC-500T       | 5"         | 4.688 | 1.438 | 6.500 | —         | 1           | 701          | 70170 |
| TRC-600T       | 6"         | 4.938 | 1.563 | 7.500 | —         | 1           | 920          | 70180 |

