

# MALLEABLE IRON RIGID SET-SCREW COUPLINGS

## FOR THREADLESS RIGID CONDUIT AND IMC

### APPLICATION:

- To couple sections of threadless rigid conduit together.

### FEATURES:

- Concrete tight.

### STANDARD MATERIALS:

Malleable Iron


### STANDARD FINISH:

Zinc Plated

### CERTIFICATIONS AND COMPLIANCES



**UL LISTED E198258**  
UL Standard: UL514B  
NEMA FB-1  
ASTM Rated



## TYPE TRCC-75

| CATALOG NUMBER | TRADE SIZE | DIM A | DIM B | DIM C | UNIT PACK | MASTER PACK | LBS./ 100 PCS | UPC # |
|----------------|------------|-------|-------|-------|-----------|-------------|---------------|-------|
| TRCC-50        | 1/2"       | 1.750 | 0.750 | 1.375 | 20        | 100         | 30            | 70820 |
| TRCC-75        | 3/4"       | 2.000 | 0.875 | 1.563 | 20        | 100         | 32            | 70821 |
| TRCC-100       | 1"         | 2.688 | 1.188 | 1.875 | 5         | 50          | 44            | 70822 |
| TRCC-125       | 1-1/4"     | 2.750 | 1.250 | 2.188 | 5         | 25          | 78            | 70823 |
| TRCC-150       | 1-1/2"     | 3.188 | 1.500 | 2.500 | 5         | 20          | 93            | 70824 |
| TRCC-200       | 2"         | 3.375 | 1.563 | 3.000 | 2         | 10          | 159           | 70825 |
| TRCC-250       | 2-1/2"     | 4.000 | 1.718 | 3.125 | 2         | 10          | 277           | 70826 |
| TRCC-300       | 3"         | 4.250 | 1.938 | 3.750 | 1         | 5           | 393           | 70827 |
| TRCC-350       | 3-1/2"     | 4.500 | 2.250 | 4.250 | 1         | 5           | 547           | 70828 |
| TRCC-400       | 4"         | 4.750 | 2.625 | 4.750 | 1         | 5           | 626           | 70829 |
| TRCC-500       | 5"         | 6.000 | 2.818 | 6.500 | —         | 1           | 1220          | 70862 |
| TRCC-600       | 6"         | 6.500 | 3.000 | 7.500 | —         | 1           | 1300          | 70863 |

