

MALLEABLE IRON 90° PULL ELBOWS FOR THREADED RIGID CONDUIT AND IMC

APPLICATION:

- For connecting rigid conduit or IMC to rigid conduit or IMC to form 90° bend.

FEATURES:

- Raintight.
- Furnished with Neoprene gasketed steel cover.
- Threaded for rigid conduit and IMC (Female-NPT).

STANDARD MATERIALS:

Malleable Iron


STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE PEF75

Female to Female

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
PEF50	1/2"	2.188	2.188	10	100	36	13701
PEF75	3/4"	2.313	2.313	5	50	49	13703
PEF100	1"	3.125	3.125	—	25	94	13704
PEF125	1-1/4"	3.625	3.625	—	20	140	13705
PEF150	1-1/2"	4.125	4.125	—	10	200	13707
PEF200	2"	4.500	4.500	—	5	345	13708

APPLICATION:

- For connecting rigid conduit or IMC to box or enclosures to form 90° bend.

FEATURES:

- Raintight.
- Furnished with Neoprene gasketed steel cover.
- Furnished with steel locknut.
- Threaded for rigid conduit and IMC (Female-NPT, Male-NPSM).

STANDARD MATERIALS:

Malleable Iron


STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE PEM75

Male to Female

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
PEM50	1/2"	2.188	2.438	0.563	10	100	36	70887
PEM75	3/4"	2.313	2.625	0.625	5	50	49	70888
PEM100	1"	3.125	3.188	0.625	—	25	94	70882
PEM125	1-1/4"	3.625	4.125	0.750	—	20	140	70883
PEM150	1-1/2"	4.125	5.188	0.813	—	10	200	90142
PEM200	2"	4.500	5.688	0.875	—	5	345	90143

