

MALLEABLE IRON ONE-HOLE STRAPS FOR THREADED RIGID CONDUIT AND IMC

APPLICATION:

- Click-on type one-hole straps for rigid conduit or IMC. Provides support for the conduits as required by the National Electrical Code.

FEATURES:

- Heavy-duty casting.

STANDARD MATERIALS:

Malleable Iron

STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198338


UL Standard: UL514B

NEMA FB-1

ASTM Rated

OPTIONAL FINISH:

For additional corrosion protection, specify Hot Dipped Galvanized. Add suffix "G" to Malleable Iron catalog number. Example 133G. For more information, see page 31.



TYPE 133

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
132	1/2"	1.437	0.625	0.312	100	1000	6	81321
133	3/4"	1.750	0.750	0.312	100	1000	8	81331
134	1"	2.125	0.937	0.312	50	500	9	81341
135	1-1/4"	2.375	1.062	0.437	—	100	22	81351
136	1-1/2"	2.750	1.062	0.500	—	50	32	81361
137	2"	3.937	1.250	0.562	—	50	44	81371
138	2-1/2"	3.937	1.250	0.562	—	25	66	81381
139	3"	5.187	1.750	0.562	—	10	159	81391
141	3-1/2"	5.562	2.125	0.750	—	10	185	81411
148	4"	6.500	2.250	0.750	—	10	221	81481
150	5"	10.040	2.750	0.750	—	5	369	81501
152	6"	12.500	3.130	0.750	—	5	631	81521

MALLEABLE IRON CLAMP BACK SPACERS FOR THREADED RIGID CONDUIT AND IMC

APPLICATION:

- Provides space between conduit and mounting surface, for use with malleable iron or aluminum straps.

FEATURES:

- Heavy-duty casting.
- Can be used with one-hole straps.

STANDARD MATERIALS:

Malleable Iron

STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198338


UL Standard: UL514B

NEMA FB-1

ASTM Rated

OPTIONAL FINISH:

For additional corrosion protection, specify Hot Dipped Galvanized. Add suffix "G" to Malleable Iron catalog number. Example 901G. For more information, see page 31.



TYPE 901

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	DIM D	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
900	1/2"	2.000	1.000	0.500	0.313	100	1000	8	89009
901	3/4"	2.300	1.060	0.500	0.313	100	500	12	89011
902	1"	2.320	1.250	0.560	0.375	50	500	16	89021
903	1-1/4"	3.430	1.870	0.750	0.438	50	250	22	89031
904	1-1/2"	3.810	1.870	0.810	0.438	—	25	35	89041
905	2"	4.750	1.920	1.000	0.563	—	25	51	89051
906	2-1/2"	5.750	2.410	1.000	0.563	—	25	81	89061
907	3"	6.780	2.620	1.000	0.563	—	25	83	89071
908	3-1/2"	7.120	2.870	1.060	0.750	—	20	148	89081
909	4"	8.830	3.060	1.060	0.750	—	10	199	89091
910	5"	10.125	3.750	1.188	0.750	—	10	344	89092
911	6"	12.188	4.000	1.500	0.750	—	10	419	89093

