

STEEL EMT COMPRESSION CONNECTORS FOR EMT CONDUIT

APPLICATION:

- To ground and secure EMT raceways to boxes and enclosures.

FEATURES:

- Male hub threads NPS.
- Concrete tight.
- Heavy steel walls.

STANDARD MATERIALS:

Steel


STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES




UL LISTED E308075
UL Standard: UL514B
NEMA FB-1
ASTM Rated
Concrete tight



TYPE S1011

CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
S1010	1/2"	1/2"	1.040	0.034	1.120	50	500	11	61007
S1011	3/4"	3/4"	1.040	0.043	1.390	25	250	17	61017
S1012	1"	1"	1.050	0.052	1.700	50	200	23	61027
S1013	1-1/4"	1-1/4"	1.270	0.062	2.050	25	100	41	61037
S1014	1-1/2"	1-1/2"	1.400	0.064	2.250	10	40	50	61047
S1015	2"	2"	1.520	0.066	2.780	5	20	67	61057
S1015D	2-1/2"	2-1/2"	2.510	0.083	3.600	—	12	177	61067
S1015E	3"	3"	2.540	0.083	4.260	—	12	234	61077
S1015E1	3-1/2"	3-1/2"	2.720	0.087	4.710	—	6	288	60187
S1015F	4"	4"	2.890	0.090	5.210	—	6	343	61097



TYPE S4061

Insulated Throat

CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
S4060	1/2"	1/2"	1.040	0.034	1.120	50	500	11	61003
S4061	3/4"	3/4"	1.040	0.043	1.390	25	250	17	61013
S4062	1"	1"	1.050	0.052	1.700	50	200	23	61023
S4063	1-1/4"	1-1/4"	1.270	0.062	2.050	25	100	41	61033
S4064	1-1/2"	1-1/2"	1.400	0.064	2.250	10	40	50	61043
S4065	2"	2"	1.520	0.066	2.780	5	20	67	61053
S4065D	2-1/2"	2-1/2"	2.510	0.083	3.600	—	12	177	61063
S4065E	3"	3"	2.540	0.083	4.200	—	12	234	61073
S4065E1	3-1/2"	3-1/2"	2.720	0.087	4.710	—	6	288	61083
S4065F	4"	4"	2.890	0.090	5.210	—	6	343	61093

