

STEEL RAIN TIGHT EMT COMPRESSION COUPLINGS

FOR EMT CONDUIT

APPLICATION:

- Compression-style coupling used to join two lengths of EMT. Internal sealing rings create a raintight seal.
- The design prevents water seepage into conduit.

FEATURES:

- The only steel compression fitting, UL Listed Raintight.
- All steel construction with zinc plated finish for corrosion resistance.
- Distinct blue gland nut provides quick raintight identification.
- Unique raised bump design affords fast, positive locking of compression nuts.
- Heavy steel walls.
- Raintight.
- Concrete tight.

STANDARD MATERIALS:

Steel


STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES



PATENTED
UL LISTED E308075
 UL Standard: UL514B
 NEMA FB-1
 ASTM Rated
 Raintight
 Concrete tight



TYPE S1017RT

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
S1016RT	1/2"	1.60	1.12	50	500	8	62401
S1017RT	3/4"	1.60	1.39	25	250	13	62402
S1018RT	1"	1.71	1.68	50	200	20	62403
S1019RT	1-1/4"	2.08	2.06	25	100	40	62404
S1020RT	1-1/2"	2.36	2.25	10	40	58	62405
S1021RT	2"	2.40	2.78	5	20	65	62406
S1021DRT	2-1/2"	3.89	3.65	—	12	130	62407
S1021ERT	3"	4.25	4.31	—	12	140	62408
S1021E1RT	3-1/2"	4.65	4.75	—	6	217	62409
S1021FRT	4"	4.90	5.27	—	6	250	62410

