

MALLEABLE IRON 90° LIQUIDTIGHT CONNECTORS

FOR LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT

APPLICATION:

- To secure, ground and seal liquidtight flexible metal conduit to boxes and enclosures.

FEATURES:

- Tapered threaded male hub NPT.
- Compact, slim diameter with small turning radius.
- Furnished with an insulated throat with steel locknut and sealing ring.
- Suitable for wet locations.
- Long ferrule prevents pullout and tight bend conduit "pop-out."

STANDARD MATERIALS:

Malleable Iron/Steel Ferrule

STANDARD FINISH:

Zinc Plated

OPTIONAL FINISH:


For additional corrosion protection, specify Hot Dipped Galvanized. Add suffix "MG" to Malleable Iron catalog number. Example SLT35TMG. For more information, see page 26.

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated
Liquidtight/Raintight/Concrete tight/Oiltight

UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following Hazardous Locations under NEC 501-4(b), 502-(a)(2); Class I, Div. 2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I



TYPE SLT35T

All Furnished with Insulated Throats

CATALOG NUMBER	TRADE SIZE	KO SIZE	I.D.	O.D.	DIM A	DIM B	DIM C	DIM D	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
SLT25T	3/8"	1/2"	0.590	0.793	1.31	0.50	1.15	1.37	10	100	28	14259
SLT35T	1/2"	1/2"	0.590	0.793	1.43	0.50	1.28	1.37	10	100	31	14690
SLT36T	3/4"	3/4"	0.785	1.020	1.62	0.52	1.55	1.50	10	100	46	14700
SLT37T	1"	1"	0.980	1.261	1.93	0.65	1.80	1.81	5	50	77	14710
SLT38T	1-1/4"	1-1/4"	1.330	1.605	2.37	0.66	2.25	1.94	—	10	98	14389
SLT39T	1-1/2"	1-1/2"	1.530	1.844	2.68	0.73	2.44	2.40	—	10	124	14399
SLT40T	2"	2"	1.995	2.337	3.18	0.75	2.97	2.64	—	5	179	14409
SLT65T	2-1/2"	2-1/2"	2.341	2.797	8.31	1.01	4.01	7.81	—	1	847	14659
SLT66T	3"	3"	2.939	3.418	9.80	1.15	4.18	9.15	—	1	1243	14669
SLT67T	3-1/2"	3-1/2"	3.406	3.915	11.18	1.18	5.25	11.22	—	1	1914	14679
SLT68T	4"	4"	3.882	4.411	12.98	1.25	5.78	12.54	—	1	2399	14689

