

ZINC 90° LIQUIDTIGHT CONNECTORS FOR LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT

APPLICATION:

- Terminate and seal liquidtight flexible metal conduit, at 90° angle, to either oiltight, liquidtight or raintight box or enclosure.

FEATURES:

- Furnished with zinc die cast locknut and sealing ring.
- Suitable for grounding (through 1-1/4").
- Suitable for wet locations.


STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES




UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated
Liquidtight/Raintight/Oiltight



TYPE LT35

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
LT25	3/8"	2.062	0.520	2.340	10	100	23	14252
LT35	1/2"	2.220	0.525	2.340	10	100	27	14352
LT36	3/4"	2.550	0.680	3.550	10	100	48	14362
LT37	1"	2.820	0.675	3.785	5	50	76	14372
LT38	1-1/4"	3.362	0.700	3.960	—	10	112	14382
LT39	1-1/2"	3.450	0.700	4.130	—	10	147	14392
LT40	2"	4.036	0.575	4.700	—	5	196	14402
LT65	2-1/2"	5.215	0.770	5.375	—	1	400	14652
LT66	3"	6.100	1.100	6.500	—	1	550	14662
LT67	3-1/2"	6.715	1.100	7.450	—	1	740	14672
LT68	4"	6.780	1.100	8.000	—	1	970	14682



TYPE LT35T

Insulated Throat

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
LT25T	3/8"	2.152	0.610	2.340	10	100	23	14258
LT35T	1/2"	2.310	0.615	2.340	10	100	27	14358
LT36T	3/4"	2.640	0.770	3.550	10	100	48	14368
LT37T	1"	2.910	0.765	3.785	5	50	76	14378
LT38T	1-1/4"	3.452	0.790	3.960	—	10	112	14388
LT39T	1-1/2"	3.540	0.790	4.130	—	10	147	14398
LT40T	2"	4.126	0.665	4.700	—	5	196	14408
LT65T	2-1/2"	5.215	0.860	5.375	—	1	400	14658
LT66T	3"	6.100	1.100	6.500	—	1	550	14668
LT67T	3-1/2"	6.715	1.100	7.450	—	1	740	14678
LT68T	4"	6.780	1.100	8.000	—	1	970	14688

