

BIG BITE SADDLE-TYPE CONNECTORS WITH INSULATED THROAT

FOR ARMORED CABLE, METAL CLAD AND FLEXIBLE METALLIC CONDUIT

APPLICATION:

- To connect Flex, AC and MC cables to a box or an enclosure.

FEATURES:

- One-piece tubular construction affording extra strength.
- Dual-gripping saddle clamps.
- Saddle clamp rides up and down on screw for ease of installation.
- Robertson head screws.
- Furnished with insulated throat.

STANDARD MATERIALS:

Tubular Steel/Steel Locknut

STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES



UL LISTED


E309514 3/8" thru 1"

E198258 1 1/4" thru 4"

UL Standard: UL514B

NEMA FB-1

ASTM Rated



TYPE DB50-IC

CATALOG NUMBER	TRADE SIZE	CABLE OPENING MAX	CABLE OPENING MIN	KO SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
*DB38-IC	3/8"	0.656	0.437	1/2"	1.188	1.250	0.500	50	500	15	31800
*DB50-IC	1/2"	0.937	0.750	1/2"	1.375	1.250	0.438	25	100	16	31801
*DB75-IC	3/4"	1.125	0.906	3/4"	1.375	1.438	0.438	10	100	17	31802
*DB100-IC	1"	1.468	1.250	1"	1.563	1.813	0.500	5	50	31	31803
DB125-IC	1-1/4"	1.500	1.312	1-1/4"	2.188	2.125	0.625	5	10	53	31804
DB150-IC	1-1/2"	1.750	1.562	1-1/2"	2.438	2.500	0.625	5	10	63	31805
DB200-IC	2"	2.031	1.812	2"	2.563	3.000	0.625	5	10	87	31806
DB250-IC	2-1/2"	3.062	2.812	2-1/2"	2.688	3.625	0.813	1	5	163	31807
DB300-IC	3"	3.562	3.312	3"	2.813	4.250	0.938	1	5	192	31808
DB350-IC	3-1/2"	4.060	3.620	3-1/2"	2.938	4.750	1.000	—	1	225	31809
DB400-IC	4"	4.560	4.120	4"	3.000	5.813	1.031	—	1	263	31810

*Suitable for use on Steel C US or Aluminum Cables.

Please see Cable Chart for Double Bite Connectors on page 169.

90° BIG BITE SADDLE-TYPE CONNECTORS WITH INSULATED THROAT

APPLICATION:

- To connect Flex, AC and MC cables to a box or an enclosure.

FEATURES:

- Male hub threads – NPSM.
- One-piece malleable construction affording extra strength.
- Dual-gripping saddle clamps.
- Saddle clamp rides up and down on screw for ease of installation.
- Robertson head screws.
- Furnished with insulated throat.

STANDARD MATERIALS:

Malleable Iron/Steel Locknuts/
Steel Clamps

STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES




UL LISTED E309514

UL Standard: UL514B

NEMA FB-1

ASTM Rated



TYPE DB5090-IC

CATALOG NUMBER	TRADE SIZE	CABLE OPENING MAX	CABLE OPENING MIN	KO SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
DB3890-IC	3/8"	0.656	0.437	1/2"	1.750	2.063	1.000	50	500	15	99916
DB5090-IC	1/2"	0.937	0.750	1/2"	2.125	2.250	1.250	25	100	16	99917
DB7590-IC	3/4"	1.125	0.906	3/4"	2.500	2.500	1.375	10	100	17	99918
DB10090-IC	1"	1.468	1.250	1"	2.813	2.875	1.688	5	50	31	99919

Please see Cable Chart for Double Bite Connectors on page 169.

