

45° BIG BITE SADDLE-TYPE CONNECTORS WITH INSULATED THROAT

FOR ARMORED CABLE, METAL CLAD AND FLEXIBLE METALLIC CONDUIT

APPLICATION:

- To connect Flex, AC and MC cables to a box or an enclosure.

FEATURES:

- Male hub threads – NPSM.
- One-piece malleable construction affording extra strength.
- Dual-gripping saddle clamps.
- Saddle clamp rides up and down on screw for ease of installation.
- Robertson head screws.
- Furnished with insulated throat.

STANDARD MATERIALS:


Malleable Iron/Steel Locknuts/
Steel Clamps

STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES

UL LISTED E309514
UL Standard: UL514B
NEMA FB-1
ASTM Rated

**TYPE DB5045-IC**

CATALOG NUMBER	TRADE SIZE	CABLE OPENING MAX	CABLE OPENING MIN	KO SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
DB3845-IC	3/8"	0.656	0.437	1/2"	1.813	1.750	0.938	50	250	16	99913
DB5045-IC	1/2"	0.937	0.750	1/2"	2.125	2.125	1.250	25	100	26	99914
DB7545-IC	3/4"	1.125	0.906	3/4"	2.375	2.313	1.438	10	100	29	99915

Please see Cable Chart for Double Bite Connectors on page 169.