

ZINC STRAIGHT CABLE CONNECTORS

FOR ARMORED CABLE AND FLEXIBLE METALLIC CONDUIT

APPLICATION:

- Used with a locknut to terminate steel or aluminum flexible metal conduit and armored cable to enclosure.

FEATURES:

- Assembled with die cast locknut and tri-combo screws.


STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258
CSA File No. LR57925
UL Standard: UL514B
NEMA FB-1
ASTM Rated




TYPE C27Z

Squeeze Type

CATALOG NUMBER	TRADE SIZE	DIM A MIN	DIM A MAX	DIM B	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
C47Z	3/8"	0.530	0.620	0.982	50	500	7	24708
C27Z	1/2"	0.850	0.914	1.470	25	250	10	32708
C28Z	3/4"	1.100	1.135	1.580	25	250	13	32808
C29Z	1"	1.255	1.375	1.750	10	100	20	32908
C30Z	1-1/4"	1.550	1.610	1.910	10	100	29	33008
C31Z	1-1/2"	1.810	1.895	2.090	5	50	39	33108
C32Z	2"	2.260	2.485	2.340	10	40	46	33208

Please see Cable Chart for Cable Connectors on page 182.



TYPE C27ZT

Squeeze Type – Insulated Throat

CATALOG NUMBER	TRADE SIZE	DIM A MIN	DIM A MAX	DIM B	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
C47ZT	3/8"	0.530	0.620	0.982	50	500	7	32646
C27ZT	1/2"	0.850	0.914	1.470	25	250	10	32757
C28ZT	3/4"	1.100	1.135	1.580	25	250	13	32867
C29ZT	1"	1.255	1.375	1.750	10	100	20	32967
C30ZT	1-1/4"	1.550	1.610	1.910	10	100	29	33067
C31ZT	1-1/2"	1.810	1.895	2.090	5	50	39	33167
C32ZT	2"	2.260	2.485	2.340	10	40	46	33267

Please see Cable Chart for Cable Connectors on page 182.

