

ZINC TWO-SCREW TAKE-ALL CONNECTORS

FOR ARMORED CABLE, METAL CLAD, FLEXIBLE METALLIC CONDUIT AND NON-METAL SHEATHED CABLE

APPLICATION:

- Used with locknut to terminate service entrance cable to enclosure.

FEATURES:

- Take-all type.


STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES




UL LISTED E309514
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE C50Z

CATALOG NUMBER	TRADE SIZE	DIM A MIN	DIM A MAX	DIM B	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
C48Z	1/2"	0.40	0.95	1.87	25	250	10	32482
C49Z	3/4"	0.50	1.10	1.84	20	200	12	32492
C50Z	1"	0.62	1.14	2.00	10	100	15	32502
C51Z	1-1/4"	0.50	1.38	2.28	10	100	25	32512
C52Z	1-1/2"	0.75	1.61	2.49	10	100	38	32522
C53Z	2"	0.90	2.04	3.35	5	50	50	32632

Please see Cable Chart for Cable Connectors on page 182.



TYPE C50ZT

Insulated

CATALOG NUMBER	TRADE SIZE	DIM A MIN	DIM A MAX	DIM B	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
C48ZT	1/2"	0.40	0.95	1.87	25	250	10	34867
C49ZT	3/4"	0.50	1.10	1.84	20	200	12	34967
C50ZT	1"	0.62	1.14	2.00	10	100	15	35067
C51ZT	1-1/4"	0.50	1.38	2.28	10	100	25	35167
C52ZT	1-1/2"	0.75	1.61	2.49	10	100	38	35267
C53ZT	2"	0.90	2.04	3.35	5	50	50	35367

Please see Cable Chart for Cable Connectors on page 182.

