

ZINC CABLE AND CONDUIT CONNECTORS

FOR ARMORED CABLE, METAL CLAD AND FLEXIBLE METALLIC CONDUIT

APPLICATION:

- For use with flexible metal conduit and reduced wall flexible metal conduit, metal clad and armored cable. They are used to connect two, Trade Size 3/8 (12) flexible metal conduits, two armored cable of appropriate size marked, or two metal clad cable of appropriate size marked to an enclosure through a Trade Size 1/2 (16) knockout.

FEATURES:

- UL Listed locknut.
- Male hub NPS.
- Tri-combo head screws.


STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258
CSA File No. LR57925
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE C270A

Duplex Single-Screw Clamp Type

CATALOG NUMBER	TRADE SIZE	DIM A MIN	DIM A MAX	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
C270A	3/8"	0.438	1.688	1.625	25	250	13	52712

Please see Cable Chart for Cable Connectors on page 182.

APPLICATION:

- Strap-type fitting used to connect flexible metal conduit or armored cable to box or enclosure.

FEATURES:

- UL Listed locknut.
- Male Hub NPS.
- Tri-combo head screws.



STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258
CSA File No. LR57925
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE C270

Duplex Two-Screw Clamp Type

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
C270	3/8"	1.688	0.438	1.625	20	200	12	52702

