

ZINC COMBINATION COUPLINGS

FOR EMT CONDUIT AND FLEXIBLE METALLIC CONDUIT

APPLICATION:

- A combination coupling to provide a transition from EMT to flexible metallic conduit.

FEATURES:

- Assembled with tri-combo screws.


STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES





UL LISTED E198258
CSA File No. LR57925
 UL Standard: UL514B
 NEMA FB-1
 ASTM Rated



TYPE 170C

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
*170C	1/2" EMT-3/8" Flex	1.280	1.140	50	500	8	51702
171C	1/2" EMT-1/2" Flex	1.645	1.340	25	250	10	51703
172C	3/4" EMT-3/4" Flex	1.975	1.535	20	200	15	51704
173C	1" EMT-1" Flex	2.285	1.700	10	100	26	51705

*EMT TO NM CABLE
 Please see Cable Chart for Cable Connectors on page 182.



TYPE 171

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
171	1/2" EMT-1/2" FMC	1.645	1.340	25	250	10	51712
172	3/4" EMT-3/4" FMC	1.975	1.535	20	200	15	51722

Please see Cable Chart for Cable Connectors on page 182.

