

# ZINC CABLE AND CONDUIT CONNECTORS

## FOR NON-METALLIC SHEATHED CABLE

**APPLICATION:**


- Used to connect non-metallic sheath cable and flexible cord from 0.290" to 0.450" in diameter to outlet boxes, enclosures or raceway systems in dry locations.

**FEATURES:**

- Assembled with die cast locknut and tri-combo screws.

**STANDARD MATERIALS:**

Zinc Die Cast

**TYPE C23****Romex Connector****CERTIFICATIONS AND COMPLIANCES**

**UL LISTED E198258**  
UL Standard: UL514B  
NEMA FB-1  
ASTM Rated

CATALOG NUMBER	TRADE SIZE	DIM A MIN.	DIM A MAX.	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
C23	3/8"	0.64	0.18	1.21	100	1000	5	31232

One or two non-metallic cable 14-2 to 12-2 or 0.29" to 0.45" diameter flexible cord  
Please see Cable Chart for Cable Connectors on Page 194.

**APPLICATION:**


- Non-watertight. To make a termination of non-metallic sheathed cable and service entrance.

**FEATURES:**

- Assembled with die cast locknut and tri-combo screws.

**STANDARD MATERIALS:**

Zinc Die Cast

**TYPE SC1****Service Entrance Connector****CERTIFICATIONS AND COMPLIANCES**

**UL LISTED E198258**  
UL Standard: UL514B  
NEMA FB-1  
ASTM Rated

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
SC1	3/4"	0.450	1.031	1.220	25	250	10	32012
SC2	1"	0.645	1.190	1.500	20	200	16	32022
SC3	1-1/4"	0.660	1.330	1.900	10	100	25	32031
SC4	1-1/2"	0.740	1.470	2.115	10	100	36	32042
SC5	2"	0.750	1.620	2.640	5	50	50	32052

Please see Cable Chart for Cable Connectors on Page 194.

CATALOG NUMBER	SE/oval diameter in.	Ser/round diameter in.
SC1 Non-Metallic Cable 10-3 through 8-2	(.52 by .61) and (.51 by .80)	(.57) and (.69)
SC2 Non-Metallic Cable 10-3 through 4-3	(.51 by .80) and (.62 by .975)	(.69) and (.92)
SC3	(1.065 by 0.635) and (1.250 by 0.740)	-
SC4	(1.065 by 0.635) and (1.250 by 0.740)	-
SC5	(1.405 by 0.875) and (1.450 by 0.875)	-



**STEELELECTRIC**  
PRODUCTS