

# GROUND CLAMPS FOR ARMORED CABLE

**APPLICATION:**

- Integral cast, lay-in lug style direct burial ground clamps are for making connection with #10AWG solid to #2 AWG stranded copper wire to 1/2" to 1" ground water pipe or 3/8" to 1" rebar. Clamps meet both UL and NEC requirements for burial in earth or embedment in concrete. Typical installations include swimming pool and service grounding.

**FEATURES:**

- Combines FOUR clamps into ONE.
- It eliminates, rebar clamp, clamp with steel screws, clamp with brass screws and direct burial clamp.
- Configure any job in 1/3 the time by presetting clamps with lay-in feature.

**STANDARD MATERIALS:**

Bronze Alloy with Stainless Steel Screws

**CERTIFICATIONS AND COMPLIANCES**

Patent Pending  
UL LISTED E93683  
UL Standard: UL514B  
NEMA FB-1  
ASTM Rated  
CSA file No. LR57925  
Listed for Direct Burial in Earth & Concrete

**TYPE RBC-50****Patent Pending Direct Burial – Ground Clamp for Rebar**

CATALOG NUMBER	PIPE RANGE	REBAR RANGE	GROUND ROD RANGE	WIRE RANGE	MECHANICAL CONNECTION/ SPLICE	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
RBC-50	1/2" - 1"	3/8" - 1"	1/4" - 1"	#10 SOL - #2 STR	TWO #8 SOL	25	250	21	66101

# GROUND CLAMPS, ROD CLAMPS AND HUBS FOR RIGID CONDUIT

**APPLICATION:**


- Used to connect grounding conductor in rigid conduit to water pipe for grounding.

**STANDARD MATERIALS:**

Solid Brass with Steel Screws

**CERTIFICATIONS AND COMPLIANCES**

UL LISTED E93683  
UL Standard: UL514B  
NEMA FB-1  
ASTM Rated

**TYPE 307**

CATALOG NUMBER	TRADE SIZE	HUB SIZE	DIM A	MIN.	MAX.	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
301	1/2" - 1"	1/2"	2.250	0.550	1.795	10	100	25	43014
302	1/2" - 1"	3/4"	2.250	0.550	1.795	10	100	30	43024
310	1/2" - 1"	1"	2.250	0.550	1.795	10	50	35	43104
307	1-1/4" - 2"	1/2"	3.600	1.390	3.000	10	50	75	43074
308	1-1/4" - 2"	3/4"	3.600	1.390	3.000	10	50	80	43084
309	1-1/4" - 2"	1"	3.600	1.390	3.600	—	25	85	43094
35C	2-1/2" - 4"	1/2"	2.430	0.500	1.380	—	10	140	43534
36C	4" - 6"	1/2"	8.000	4.000	7.900	—	2	175	43634
35D	2-1/2" - 4"	3/4"	2.430	0.500	1.380	—	10	185	43544
36D	4" - 6"	3/4"	8.000	4.000	7.900	—	2	215	43644
35E	2-1/2" - 4"	1"	2.430	0.500	1.380	—	10	225	43554
36E	4" - 6"	1"	8.000	4.000	7.900	—	2	280	43654