

CONDUIT CLAMPS

FOR THREADED RIGID CONDUIT, IMC AND EMT CONDUIT

APPLICATION:

- Used to secure conduit or EMT across, parallel or perpendicular to beam, channel and angle supports.

FEATURES:

- Easily Installed.
- Capable of withstanding heavy loads.
- A Hot Dipped Galvanized finish provides a plating thickness equivalent to hot dip process meeting ASTM A-153 performance criteria.

STANDARD MATERIALS:

Malleable Iron with Steel U-Bolts and Nuts


STANDARD FINISH:

Hot Dip Galvanized

CERTIFICATIONS AND COMPLIANCES




UL LISTED E198338
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE RA75

Right Angle-Type Conduit Clamps

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	DIM D	DIM E	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
RA50	1/2"	1.000	1.250	2.500	1.813	2.063	—	50	34	74050
RA75	3/4"	1.125	1.375	2.813	1.813	2.250	—	50	38	74075
RA100	1"	1.375	1.625	3.063	1.813	2.563	—	50	45	74100
RA125	1-1/4"	1.750	2.000	3.188	1.813	2.875	—	25	49	74125
RA150	1-1/2"	2.000	2.375	3.500	1.813	3.250	—	25	54	74150
RA200	2"	2.500	2.500	4.500	2.625	4.063	—	25	71	74200
RA250	2-1/2"	3.000	3.250	4.875	2.625	4.500	—	10	90	74250
RA300	3"	3.625	3.875	5.375	2.625	5.125	—	10	101	74300
RA350	3-1/2"	4.063	4.563	5.875	2.625	5.625	—	10	110	74350
RA400	4"	4.688	5.063	6.688	2.625	6.125	—	10	128	74400



TYPE PAR50

Parallel-Type Conduit Clamps

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
PAR50	1/2"	2.875	1.438	—	50	54	75550
PAR75	3/4"	3.063	1.688	—	50	61	75551
PAR100	1"	3.250	2.000	—	50	62	75552
PAR125	1-1/4"	3.625	2.125	—	25	82	75553
PAR150	1-1/2"	3.875	2.188	—	25	85	75554
PAR200	2"	4.625	2.875	—	25	103	75556
PAR250	2-1/2"	5.250	3.250	—	10	127	75557
PAR300	3"	5.875	3.875	—	10	154	75558
PAR350	3-1/2"	6.313	4.313	—	10	163	75559
PAR400	4"	6.813	4.813	—	10	180	75560

