

CONDUIT BEAM CLAMPS FOR THREADED RIGID CONDUIT

APPLICATION:

- Provides support for conduit hanging systems.

FEATURES:

- Steel bolt – case hardened
- Standard Sizes: 1"-2-1/2".
Jaw Opening: 3/4"-1-1/4".

STANDARD MATERIALS:

Malleable Iron/Steel
Bolt-Case Hardened


STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198338
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE 620

CATALOG NUMBER	TRADE SIZE	TAP SIZE	JAW OPENING	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
620	1"	1/4" – 20"	0.750	1.125	1.400	1.385	25	250	22	16201
621	1"	3/8" – 16"	0.750	1.125	1.400	1.385	25	250	22	16211
625	2"	3/8" – 16"	0.875	1.990	1.755	1.885	—	50	90	16251
626	2"	1/2" – 13"	0.875	1.990	1.755	1.885	—	25	90	16261
627	2-1/2"	1/2" – 13"	1.250	2.530	2.140	2.500	—	25	160	16271

Loading Capacity

CATALOG NUMBER	TRADE SIZE	WORKING LOAD	TEST LOAD FOR 5 MIN.
620	1"	250 LBS	750 LBS
621	1"	250 LBS	750 LBS
625	2"	500 LBS	1500 LBS
626	2"	500 LBS	1500 LBS
627	2-1/2"	500 LBS	1500 LBS

APPLICATION:

- Clamp on to structure member to provide mounting means for the attachment of conduit hangers either directly or by means of threaded rod.

STANDARD MATERIALS:

Steel


STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES



UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE S620

Insulator Supports

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
S620	1/4" – 20"	0.920	1.400	1.625	25	250	15	16207

