

# ZINC NON-WATERTIGHT SHORT BODY CONNECTORS

## FOR NON-METALLIC SHEATHED CABLE AND SERVICE ENTRANCE CABLE

**APPLICATION:**

- Used with locknut to terminate service entrance cable to enclosure.

**FEATURES:**


- Assembled with die cast locknut and tri-combo screws.
- For round cable.

**STANDARD MATERIALS:**

Zinc Die Cast

**CERTIFICATIONS AND COMPLIANCES**



**UL LISTED E198258**  
UL Standard: UL514B  
NEMA FB-1  
ASTM Rated



### TYPE C50S

CATALOG NUMBER	TRADE SIZE	DIM. A MIN.	DIM. A MAX.	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
C50S	1"	0.620	1.140	1.500	10	100	15	64601
C51S	1-1/4"	0.700	1.380	1.900	10	100	24	64602
C52S	1-1/2"	0.750	1.610	2.115	10	100	34	64603
C53S	2"	0.900	2.040	2.640	5	50	46	64604

Please see Cable Chart for Cable Connectors on page 218.



### TYPE C50ST

Insulated

CATALOG NUMBER	TRADE SIZE	DIM. A MIN.	DIM. A MAX.	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
C50ST	1"	0.620	1.140	1.500	10	100	15	90138
C51ST	1-1/4"	0.700	1.380	1.900	25	250	24	90139
C52ST	1-1/2"	0.750	1.610	2.115	25	250	34	90140
C53ST	2"	0.900	2.040	2.640	10	100	46	90141

Please see Cable Chart for Cable Connectors on page 218.

CATALOG NUMBER	SE/oval diameter in.	Ser/round diameter in.
C50S and C50ST Non-Metallic Cable 10-3 through 4-3	(.51 by .80) and (.62 by .975)	(.69) and (.92)
C50S and C50ST Non-Metallic Cable 4-3 through 2-3	(.67 by 1.06) and (.73 by 1.235)	1.19
C52S and C52ST	(1.15 by 0.73) and (1.41 by 0.89)	1.48
C52S and C52ST	(1.405 by 0.875) and (1.450 by 0.875)	—