

# ANTI-SHORT BUSHINGS AND ROD COUPLINGS

## THERMOPLASTIC

**APPLICATION:**


- These anti-short bushings are used in the terminations of flexible metal conduit and armored cables. Inserted into I.D. of each termination point to protect the conductors from the sharp edges of the raceway where cut.

**FEATURES:**

- Features high dielectric strength and ensures complete insulation on all sharp edges.

**STANDARD MATERIALS:**

Plastic



### TYPE 0

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	FOR CABLE SIZES	PC. PER BAG	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
0	5/16"	0.57	0.64	14-2, 14-3, 12-2, Armored Cable; 5/169 Flexible Conduit	35	1 BAG	500 BAGS	3	55506
1	3/8"	0.67	0.66	14-4, 12-3, 6-1, 4-1, Armored Cable; 3/89 Flexible Conduit	35	1 BAG	400 BAGS	3	55516
2	7/16"	0.61	0.82	12-4, 10-2, 10-3, 2-1, Armored Cable; 7/169 Flexible Conduit	35	1 BAG	300 BAGS	7	55526
3	1/2"	0.67	0.94	10-4, 8-2, 8-3, 1-1, Armored Cable; 1/29 Flexible Conduit	20	1 BAG	200 BAGS	8	55536
4	3/4"	0.79	1.16	8-4, 6-2, 6-3, Armored Cable; 3/49 Flexible Conduit	16	1 BAG	150 BAGS	6	55546

**STANDARD MATERIALS:**

Steel

**STANDARD FINISH:**

Zinc Plated



### TYPE 120R

**Rod Couplings**

CATALOG NUMBER	TRADE SIZE	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
118R	1/4" – 20"	100	1000	2	11187
120R	3/8" – 16"	100	1000	4	11207
121R	1/2" – 13"	100	1000	6	11217