


LAY-IN GROUNDING LUGS

FEATURES:

- Each lug takes a range of cable sizes.
- Heavy-duty slotted or hex head screw.
- Both aluminum and copper lay-in lugs are suitable for use with copper or aluminum conductors.



STANDARD MATERIALS:

Aluminum

STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES



UL LISTED E93683
UL Standard: UL514B
NEMA FB-1
ASTM Rated

TYPE AL4

Aluminum

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
AL4	4/14	1.063	0.375	0.750	—	100	2	10001
AL1/0	1/0 – 8	1.500	0.625	1.125	—	100	7	10002
AL250	250MCM – 6	2.188	0.813	1.688	—	50	19	10004

AL4 and AL1/0 are furnished with slotted screws. AL250 is furnished with hex-head screws.

STANDARD MATERIALS:

Copper


STANDARD FINISH:

Natural

CERTIFICATIONS AND COMPLIANCES



UL LISTED E93683
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE CL4

Copper

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
CL4	4/14	1.063	0.375	0.750	—	100	4	10005
CL1/0	1/0 – 8	1.500	0.625	1.125	—	100	16	10006
CL250	250MCM – 6	2.188	0.813	1.688	—	50	50	10008

CL4 and CL1/0 are furnished with slotted screws. CL250 is furnished with hex-head screws.