


MALLEABLE IRON/HOT DIPPED GALVANIZED WATERTIGHT CONDUIT HUBS FOR THREADED RIGID CONDUIT AND IMC

APPLICATION:

- General Purpose Fitting. Insulated Throat form with Bonding Screw.

FEATURES:

- Male thread type.
- Tapered female thread for rigid conduit and IMC.
- Recessed O-ring seal ensures watertight and dust tight connections.
- Insulated throat and bonding locknut is suitable for service entrance application.



TYPE CHM50G

MATERIAL/FINISH:

Malleable Iron

STANDARD FINISH:

Hot Dipped Galvanized/Zinc Plated

OPTIONAL FINISH:

For Malleable Iron/Zinc Plated, please remove suffix "G" from Hot Dipped Galvanized Catalog Number and see page 97.

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258

UL Standard: UL514B

NEMA FB-1

ASTM Rated

Suitable for use in hazardous locations as follows: Class I, Div. 2 Class II, Div. I, 2 Class III, Div. I, 2 Per NEC 501-4 (b), 502-4 (a), 503-3 (a)

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC#
CHM50G	1/2"	0.813	0.625	1.500	25	250	18	70910
CHM75G	3/4"	0.938	0.625	1.813	25	250	25	70911
CHM100G	1"	1.063	0.750	2.063	10	100	39	70912
CHM125G	1-1/4"	1.250	0.750	2.625	5	25	54	70913
CHM150G	1-1/2"	1.250	0.813	3.125	2	20	64	70914
CHM200G	2"	1.250	0.813	3.563	2	20	98	70915
CHM250G	2-1/2"	1.625	1.188	4.125	—	10	196	70916
CHM300G	3"	1.750	1.250	4.938	—	5	282	70917
CHM350G	3-1/2"	1.813	1.313	5.750	—	5	351	70918
CHM400G	4"	1.938	1.375	6.188	—	5	395	70919
CHM500G	5"	2.063	1.438	7.625	—	1	717	70920
CHM600G	6"	2.125	1.563	8.813	—	1	888	70921


MALLEABLE IRON/HOT DIPPED GALVANIZED 3-PIECE COUPLINGS

APPLICATION:

- Used to join two lengths of threaded conduit.

FEATURES:

- Threaded (NPS) for rigid conduit and IMC.
- Concrete tight.



TYPE 1023G

STANDARD MATERIALS:

Malleable Iron

STANDARD FINISH:

Hot Dipped Galvanized/Zinc Plated

OPTIONAL FINISH:

For Malleable Iron/Zinc Plated, please remove suffix "G" from Hot Dipped Galvanized Catalog Number and see page 101.

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258

UL Standard: UL514B

NEMA FB-1

ASTM Rated

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC#
1022G	1/2"	1.38	1.36	1.36	20	200	26	10009
1023G	3/4"	1.63	1.58	1.58	10	100	37	10210
1024G	1"	1.81	1.89	1.89	—	20	55	10011
1025G	1-1/4"	2.19	2.38	2.38	—	20	111	10012
1026G	1-1/2"	2.31	2.83	2.83	—	10	172	10013
1027G	2"	2.44	3.29	3.29	—	10	203	10014
1028G	2-1/2"	3.19	4.08	4.08	2	10	327	10015
1029G	3"	3.31	4.67	4.67	2	10	442	10016
1030G	3-1/2"	3.50	5.07	5.07	1	5	608	10017
1031G	4"	3.75	5.75	5.75	1	5	718	10018
1005G	5"	3.69	6.88	7.50	—	1	1050	10019
1006G	6"	4.31	8.00	8.00	—	1	1250	10020

