


MALLEABLE IRON/**HOT DIPPED GALVANIZED** 45° LIQUIDTIGHT CONNECTORS FOR LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT

APPLICATION:

- To secure, ground and seal Liquidtight Flexible Metal conduit to boxes and enclosures.

FEATURES:

- Tapered threaded male hub NPT.
- Compact, slim diameter with small turning radius.
- Furnished with an insulated throat with steel locknut and sealing ring.
- Liquidtight/Raintight/Oiltight.
- Suitable for wet locations.
- Long ferrule prevents pullout and tight bend conduit "pop-out."



STANDARD MATERIALS:

Malleable Iron/Steel Ferrule

STANDARD FINISH:

Hot Dipped Galvanized/Zinc Plated



OPTIONAL FINISH:

For Malleable Iron/Zinc Plated, please remove suffix "MG" from Hot Dipped Galvanized Catalog Number and see page 148.

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258

UL Standard: UL514B

NEMA FB-1

ASTM Rated

Liquidtight/Raintight/Concrete tight/Oiltight

UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following Hazardous Locations under NEC 501-4(b), 502-4(a)(2); Class I, Div.2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-1.

TYPE SLT35-45TMG

All Furnished with Insulated Throats

CATALOG NUMBER	TRADE SIZE	K.O. SIZE	I.D.	O.D.	DIM A	DIM B	DIM C	DIM D	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
SLT35-45TMG	1/2"	1/2"	0.590	0.793	1.64	0.50	1.28	1.51	10	100	29	16407
SLT36-45TMG	3/4"	3/4"	0.785	1.020	1.68	0.52	1.55	1.54	10	100	42	16412
SLT37-45TMG	1"	1"	0.980	1.261	2.16	0.65	1.80	1.81	5	50	66	16417
SLT38-45TMG	1-1/4"	1-1/4"	1.330	1.605	2.50	0.66	2.25	2.16	—	10	90	16422
SLT39-45TMG	1-1/2"	1-1/2"	1.530	1.844	3.10	0.73	2.44	2.43	—	10	112	16427
SLT40-45TMG	2"	2"	1.995	2.337	3.28	0.75	2.97	2.82	—	5	179	16432
SLT65-45TG	2-1/2"	2-1/2"	2.341	2.797	6.67	1.01	4.01	4.41	—	1	582	16437
SLT66-45TG	3"	3"	2.939	3.418	8.01	1.15	4.18	5.50	—	1	869	16442
SLT67-45TG	3-1/2"	3-1/2"	3.406	3.915	9.55	1.18	5.25	5.93	—	1	1296	16447
SLT68-45TG	4"	4"	3.882	4.411	10.64	1.25	5.78	8.34	—	1	1539	16452

