

MALLEABLE IRON/**HOT DIPPED GALVANIZED** 90° LIQUIDTIGHT CONNECTORS


WITH COPPER LUGS FOR LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT

APPLICATION:

- Connects conduit and terminates bonding conductor run externally across liquidtight conduit.

FEATURES:

- Tapered threaded male hub NPT.
- Compact, slim diameter with small turning radius.
- Furnished with Insulated throat, steel locknut and sealing ring.
- Liquidtight/Raintight/Oiltight.
- Suitable for grounding and wet locations.
- Long ferrule prevents pullout and tight bend conduit "pop-out."



STANDARD MATERIALS:

Malleable Iron/Steel Ferrule/Copper Grounding Lug

STANDARD FINISH:

Hot Dipped Galvanized/Zinc Plated



OPTIONAL FINISH:

For Malleable Iron/Zinc Plated, please remove suffix "MG" from Hot Dipped Galvanized Catalog Number and see page 153.

CERTIFICATIONS AND COMPLIANCES



UL LISTED E93683

UL Standard: UL514B

NEMA FB-1

ASTM Rated

Liquidtight/Raintight/Concrete tight/Oiltight

UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following Hazardous Locations under NEC 501-4(b), 502-4(a)(2); Class I, Div.2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I

TYPE SLT35CLTMG

All Furnished with Insulated Throats

CATALOG NUMBER	TRADE SIZE	LUG SIZE	I.D.	O.D.	DIM A	DIM B	DIM C	DIM D	DIM E	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
SLT35CLTMG	1/2"	#4-#14	0.590	0.793	1.43	0.50	1.28	1.37	0.75	10	100	20	16405
SLT36CLTMG	3/4"	#4-#14	0.785	1.020	1.62	0.52	1.55	1.54	0.75	10	100	31	16410
SLT37CLTMG	1"	#4-#14	0.980	1.261	1.93	0.65	1.80	1.81	0.75	5	50	42	16415
SLT38CLTMG	1-1/4"	#4-#14	1.330	1.605	2.37	0.66	2.25	1.94	0.75	—	10	57	16420
SLT39CLTMG	1-1/2"	#4-#14	1.530	1.844	2.68	0.73	2.44	2.40	0.75	—	10	73	16425
SLT40CLTMG	2"	#4-#14	1.995	2.337	3.18	0.75	2.97	2.64	0.75	—	5	101	16430
SLT65CLTG	2-1/2"	#1/0-#8	2.341	2.797	8.31	1.01	4.01	7.81	1.13	—	1	373	16435
SLT66CLTG	3"	#1/0-#8	2.939	3.418	9.80	1.15	4.18	9.15	1.13	—	1	465	16440
SLT67CLTG	3-1/2"	#6-#250 MCM	3.406	3.915	11.18	1.18	5.25	11.22	1.50	—	1	686	16445
SLT68CLTG	4"	#6-#250 MCM	3.882	4.411	12.93	1.25	5.78	12.54	1.50	—	1	1539	16452

