

CONDUIT CAPPED BUSHINGS

FOR THREADED RIGID CONDUIT AND IMC

FEATURES:

- Bushings are supplied with metal cap insert.


STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES



UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE 820Z

Zinc Die Cast - Metal Capped

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
820Z	1/2"	1.15	0.47	100	1000	2	18202
821Z	3/4"	1.41	0.47	100	1000	4	18212
822Z	1"	1.68	0.54	50	500	6	18222
823Z	1-1/4"	1.94	0.60	25	250	9	18232
824Z	1-1/2"	2.20	0.62	25	250	13	18241
825Z	2"	2.80	0.62	—	25	17	18252
838Z	2-1/2"	3.32	0.93	—	25	35	18382
839Z	3"	3.94	0.93	10	100	48	18392
840Z	3-1/2"	4.45	0.94	5	25	57	18402
841Z	4"	5.00	0.97	5	25	81	18412
*842MI	5"	6.13	1.13	—	25	130	90110
*843MI	6"	7.19	1.13	—	10	195	90111

* 5" & 6" Capped Bushings in Malleable Iron.

CONDUIT METAL PENNIES

FOR THREADED RIGID CONDUIT AND IMC

APPLICATION:

- Used to insert into zinc die cast or malleable iron bushing.

STANDARD MATERIALS:

Steel

CERTIFICATIONS AND COMPLIANCES



UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE 535M

Metal Pennies

CATALOG NUMBER	TRADE SIZE	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
533M	1-1/4"	—	100	2	15331
534M	1-1/2"	—	100	2	15341
535M	2"	—	50	3	15351
536M	2-1/2"	—	50	5	15361
537M	3"	—	50	6	15371
538M	3-1/2"	—	25	10	15381
539M	4"	—	25	12	15391
559M	5"	—	10	13	15591
569M	6"	—	10	15	15691

