

PLASTIC BUSHINGS

FOR THREADED RIGID CONDUIT AND IMC

APPLICATION:

- Threaded plastic bushings are used at the end of threaded conduit or conduit connector, to provide smooth well rounded bearing surface for wires or cables as required by the National Electrical Code.

FEATURES:

- Thermoplastic material-heat, impact and torque resistance.
- Meets UL and CSA specifications.


STANDARD MATERIALS:

Flame-Retardant
Polypropylene.
(Rated to 221° F, 105° C)

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE ST10

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS. / 100 PCS	UPC #
ST10	1/2"	1.03	0.37	100	1000	1	51068
ST11	3/4"	1.28	0.39	100	1000	1	51168
ST12	1"	1.65	0.50	50	500	2	51268
ST13	1-1/4"	2.10	0.49	25	250	2	51368
ST14	1-1/2"	2.28	0.49	25	250	4	51468
ST15	2"	2.66	0.54	—	100	5	51568
ST16	2-1/2"	3.31	0.63	—	25	6	51668
ST17	3"	3.95	0.70	—	25	7	51768
ST18	3-1/2"	4.41	0.71	—	25	8	51868
ST19	4"	4.94	0.73	—	25	9	51968
ST20	5"	6.38	1.00	—	5	32	52068
ST21	6"	7.50	0.99	—	5	40	52168

