

MALLEABLE IRON CONDUIT NIPPLES FOR THREADED RIGID CONDUIT AND IMC

APPLICATION:

- Used through knockout to connect box to conduit coupling. Used with a locknut to connect two boxes side by side or back to back. Used with a locknut to connect fixture housing to continuous runs.

FEATURES:

- Available with insulated throat.
- With rigid conduit threads (NPS).

STANDARD MATERIALS:

Malleable Iron



STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES





UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE 90

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
90	1/2"	1.050	0.585	100	1000	6	19001
91	3/4"	1.310	0.545	100	1000	8	19101
92	1"	1.640	0.710	50	500	15	19201
93	1-1/4"	2.095	0.840	25	250	24	19301
94	1-1/2"	2.410	0.835	—	25	28	19401
95	2"	2.945	0.900	—	25	38	19501
96	2-1/2"	3.955	1.200	—	15	71	19601
97	3"	4.390	1.490	—	10	124	19701
98	3-1/2"	4.925	1.395	—	10	163	19801
99	4"	5.420	1.395	—	10	199	19901
995	5"	6.950	1.800	—	5	331	19951
996	6"	8.370	2.165	—	5	441	19961



TYPE 90T

Insulated Throat

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
90T	1/2"	1.050	0.585	100	1000	6	19003
91T	3/4"	1.310	0.545	100	1000	8	19103
92T	1"	1.640	0.710	50	500	15	19203
93T	1-1/4"	2.095	0.840	25	250	24	19303
94T	1-1/2"	2.410	0.835	—	25	28	19403
95T	2"	2.945	0.900	—	25	38	19503
96T	2-1/2"	3.955	1.200	—	15	72	19603
97T	3"	4.390	1.490	—	10	125	19703
98T	3-1/2"	4.925	1.395	—	10	166	19803
99T	4"	5.420	1.395	—	10	202	19903
995T	5"	6.950	1.800	—	5	336	19953
996T	6"	8.370	2.165	—	5	448	19963

