

# WATERTIGHT CONDUIT HUBS FOR THREADED RIGID CONDUIT AND IMC

## APPLICATION:

- To secure threaded rigid service entrance conduit to box or enclosure. Insulated throat rated 105° C. BUNA-N sealing ring completely encircles knockout to prevent contaminants from entering enclosure.


## FEATURES:

- Assembled with 105°C rated flame retardant Lexan throat insulator and BUNA-N sealing ring.
- UL Listed and CSA Certified for use in wet locations.
- Meets NEMA sealing requirements for Type 2, 3, 3R, 4, 4X, 5, 12 and 13 enclosures.
- Certified for use in hazardous locations, Class II, Groups E, F, G and Class III.

## STANDARD MATERIALS:

Zinc Die Cast

## TYPE TWH20



## CERTIFICATIONS AND COMPLIANCES



**UL LISTED E198258**  
UL Standard: UL514B  
NEMA FB-1  
ASTM Rated



**CSA CERTIFIED**  
C5F17

NOTE: Minimum wall thickness that can be accommodated is 1/32"

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
TWH10	1/2"	1.450	1.210	25	250	16	70010
TWH20	3/4"	1.570	1.430	25	250	22	70020
TWH30	1"	1.865	1.850	10	100	41	70030
TWH40	1-1/4"	1.985	2.280	5	25	55	70040
TWH50	1-1/2"	2.040	2.555	2	20	68	70050
TWH60	2"	2.150	3.060	2	20	95	70060
TWH70	2-1/2"	2.550	3.580	—	10	165	70070
TWH80	3"	2.625	4.190	—	5	216	70080
TWH90	3-1/2"	2.655	4.780	—	5	260	70090
TWH100	4"	2.680	5.355	—	5	338	70100