

# MALLEABLE IRON CORD GRIP STRAIN RELIEF CONNECTORS

COLOR CODED - 90°

## APPLICATION

To secure and seal cords or cables entering enclosures or raceways.

## FEATURES

- Neoprene Grommet for a moisture proof seal
- Simple installation, cord can be installed without disassembly of the fitting
- Liquidtight/Oiltight/Raintight
- Suitable for NEMA 4 enclosures and other wet locations
- Male tapered thread NPT
- Colored gripper allows for easy identification

## STANDARD MATERIALS

Malleable Iron Body/Steel Gland Nut/  
Neoprene Grommet

## STANDARD FINISH

Zinc Plated



**TYPE CG50-25090**

CATALOG NUMBER	TRADE SIZE	COLOR	CABLE RANGE		UNIT PACK	MASTER PACK	LBS. / 100 PCS.	UPC #
			MIN	MAX				
<b>1/2"</b>								
CG50-25090	1/2"	Red	0.15	0.25	25	100	10	85501
CG50-35090	1/2"	White	0.25	0.35	25	100	10	85502
CG50-45090	1/2"	Blue	0.34	0.45	25	100	10	85503
CG50-56090	1/2"	Green	0.45	0.56	25	100	10	85504
CG50-65090	1/2"	Brown	0.55	0.65	25	100	10	85505
<b>3/4"</b>								
CG75-25090	3/4"	Red	0.15	0.25	10	50	14	85601
CG75-35090	3/4"	White	0.25	0.35	10	50	14	85602
CG75-45090	3/4"	Blue	0.35	0.45	10	50	14	85603
CG75-56090	3/4"	Green	0.45	0.56	10	50	14	85604
CG75-65090	3/4"	Brown	0.55	0.65	10	50	14	85605
CG75-75090	3/4"	Yellow	0.65	0.75	10	50	14	85606
CG75-85090	3/4"	Purple	0.75	0.85	10	50	14	85607
<b>1"</b>								
CG100-56090	1"	Green	0.45	0.56	5	25	20	85701
CG100-65090	1"	Brown	0.50	0.65	5	25	20	85702
CG100-75090	1"	Yellow	0.65	0.75	5	25	20	85703
CG100-85090	1"	Purple	0.75	0.85	5	25	20	85704
CG100-95090	1"	Grey	0.85	0.95	5	25	20	85705
CG100-105090	1"	Black	0.95	1.05	5	25	20	85706
<b>1-1/4"</b>								
CG125-85090	1-1/4"	Purple	0.75	0.85	5	25	40	85801
CG125-95090	1-1/4"	Grey	0.85	0.95	5	25	40	85802
CG125-105090	1-1/4"	Black	0.95	1.05	5	25	40	85803
CG125-115090	1-1/4"	Orange	1.05	1.15	5	25	40	85804
CG125-125090	1-1/4"	Red	1.15	1.25	5	25	40	85805
CG125-137590	1-1/4"	White	1.25	1.38	5	25	40	85806
<b>1-1/2"</b>								
CG150-105090	1-1/2"	Black	0.95	1.05	2	10	70	85901
CG150-115090	1-1/2"	Orange	1.05	1.15	2	10	70	85902
CG150-125090	1-1/2"	Red	1.15	1.25	2	10	70	85903
CG150-137590	1-1/2"	White	1.25	1.38	2	10	70	85904

Suitable for use in Hazardous Locations under NEC 501-4(b), 502-4(a), and 503-3(a). For Class I, Div. 2, Class II, Div. 1, 2, and Class III, Div. 1, 2.