

ZINC 90° PULL ELBOWS FOR THREADED RIGID CONDUIT AND IMC

APPLICATION:

- For connecting rigid conduit or IMC to rigid conduit or IMC to form 90° bend.

FEATURES:

- Raintight.
- Furnished with Neoprene gasket.


STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE 1313

Female to Female

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS. / 100 PCS	UPC #
1313	1/2"	1.31	1.09	10	100	28	13132
1314	3/4"	1.43	1.29	5	50	33	13142
1315	1"	1.95	1.59	—	25	62	13152
1316	1-1/4"	2.26	1.97	—	20	91	13162

APPLICATION:

- For connecting rigid conduit or IMC to box or enclosures to form 90° bend.

FEATURES:

- Removable aluminum cover and neoprene gasket facilitate wire pulling.
- Assembled with Zinc Die Cast Locknut.


STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE 1320

Male to Female

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS. / 100 PCS	UPC #
1320	1/2"	1.31	1.09	10	100	36	13202
1321	3/4"	1.47	1.29	5	50	49	13212

