

ZINC STRAIGHT LIQUIDTIGHT CONNECTORS FOR LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT

APPLICATION:

- Terminate and seal liquidtight flexible metal conduit to either oiltight, liquidtight or raintight box or enclosure. Connectors can be used with tapered thread female entry or unthreaded knockout using the provided sealing washer and locknut.

FEATURES:

- Furnished with zinc die cast locknut and sealing ring.
- Suitable for grounding (through 1-1/4").
- Suitable for wet locations.


STANDARD MATERIALS:

Zinc Die Cast

CERTIFICATIONS AND COMPLIANCES




UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated
Liquidtight/Raintight/Oiltight



TYPE LT27

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
LT47	3/8"	1.440	0.400	1.260	25	250	16	14472
LT27	1/2"	1.500	0.420	1.385	25	250	20	14272
LT28	3/4"	1.600	0.420	1.720	10	100	28	14282
LT29	1"	1.785	0.550	1.900	5	50	44	14292
LT30	1-1/4"	1.900	0.546	2.290	5	50	64	14302
LT31	1-1/2"	2.737	0.520	2.633	—	10	87	14312
LT32	2"	2.080	0.585	3.156	—	5	121	14322
LT33	2-1/2"	3.025	0.775	4.205	—	1	250	14332
LT34	3"	3.530	0.920	4.910	—	1	355	14342
LT60	3-1/2"	3.660	0.920	5.470	—	1	480	14602
LT61	4"	3.875	0.987	5.925	—	1	570	14612



TYPE LT27T

Insulated Throat

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC #
LT47T	3/8"	1.530	0.490	1.260	25	250	16	14478
LT27T	1/2"	1.590	0.510	1.385	25	250	20	14278
LT28T	3/4"	1.690	0.510	1.720	10	100	28	14288
LT29T	1"	1.875	0.530	1.900	5	50	44	14298
LT30T	1-1/4"	1.990	0.636	2.290	5	50	64	14308
LT31T	1-1/2"	2.207	0.610	2.633	—	10	87	14318
LT32T	2"	2.170	0.675	3.156	—	5	121	14328
LT33T	2-1/2"	3.025	0.775	4.205	—	1	250	14338
LT34T	3"	3.530	0.920	4.910	—	1	355	14348
LT60T	3-1/2"	3.660	0.920	5.470	—	1	480	14608
LT61T	4"	3.875	0.987	5.925	—	1	570	14618

