

MALLEABLE IRON RAIN-TIGHT RIGID COMPRESSION CONNECTORS

FOR THREADLESS RIGID CONDUIT AND IMC



APPLICATION:

- To connect threadless rigid conduit to boxes and enclosures creating a raintight seal.

FEATURES:

- Raintight and concrete tight male hub threads.
- NPSM Thread 1/2" through 2".
- NPT Thread above 2".

STANDARD MATERIALS:

Malleable Iron


STANDARD FINISH:

Zinc Plated

CERTIFICATIONS AND COMPLIANCES




UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated
Raintight
Concrete tight



TYPE NTC-50RT

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
NTC-50RT	1/2"	1.500	0.500	1.500	25	250	20	14215
NTC-75RT	3/4"	1.500	0.500	1.625	25	250	22	14225
NTC-100RT	1"	1.688	0.563	2.000	10	100	34	14235
NTC-125RT	1-1/4"	2.000	0.688	2.375	5	50	52	14245
NTC-150RT	1-1/2"	2.063	0.688	2.625	2	20	65	14255
NTC-200RT	2"	2.250	0.875	3.313	5	25	107	14274
NTC-250RT	2-1/2"	2.936	1.250	3.750	1	10	243	14276
NTC-300RT	3"	3.125	1.375	4.250	1	5	295	14284
NTC-350RT	3-1/2"	3.125	1.375	4.750	1	5	383	14289
NTC-400RT	4"	3.375	1.500	5.313	1	5	467	14286



TYPE NTC-50TRT

Insulated Throat

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./ 100 PCS	UPC #
NTC-50TRT	1/2"	1.563	0.563	1.500	25	250	21	14216
NTC-75TRT	3/4"	1.563	0.563	1.625	25	250	23	14226
NTC-100TRT	1"	1.750	0.625	2.000	10	100	34	14236
NTC-125TRT	1-1/4"	2.000	0.688	2.375	5	50	53	14246
NTC-150TRT	1-1/2"	2.125	0.750	2.625	2	20	66	14256
NTC-200TRT	2"	2.313	0.813	3.313	5	25	114	14275
NTC-250TRT	2-1/2"	3.000	1.313	3.750	1	10	245	14277
NTC-300TRT	3"	3.125	1.438	4.250	1	5	298	14285
NTC-350TRT	3-1/2"	3.188	1.500	4.750	1	5	387	14290
NTC-400TRT	4"	3.438	1.563	5.313	1	5	472	14287

