

MALLEABLE IRON/**HOT DIPPED GALVANIZED** FS AND FD DEVICE BOXES—SINGLE GANG FOR THREADED RIGID CONDUIT AND IMC



APPLICATION:

- Accommodates wiring devices and provides opening to splice, tap or pull conductors.

FEATURES:

- Tapered threaded hubs (NPT) with integral bushing.
- Internal grounding screw.
- Suitable for use in wet locations when used with gasketed covers.
- Surface mounting lugs.

STANDARD FINISH:

Hot Dipped Galvanized/Zinc Plated




OPTIONAL FINISH:

For Malleable Iron/Zinc Plated, please remove the "G" suffix from Hot Dipped Galvanized catalog number and see page 72.

CERTIFICATIONS AND COMPLIANCES




UL LISTED E198259
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE FD-50G

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC#
FS-50G	1/2"	5.250	2.938	2.125	1	5	221	90168
FS-75G	3/4"	5.250	2.938	2.125	1	5	233	90170
FS-100G	1"	5.250	2.938	2.125	1	5	242	90172
FD-50G	1/2"	5.250	3.000	2.875	1	5	272	90174
FD-75G	3/4"	5.250	3.000	2.875	1	5	278	90176
FD-100G	1"	5.250	3.000	2.875	1	5	283	90178



TYPE FSC-50G

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC#
FSC-50G	1/2"	6.063	2.938	2.125	1	5	234	90218
FSC-75G	3/4"	6.063	2.938	2.125	1	5	240	90220
FSC-100G	1"	6.063	2.938	2.125	1	5	250	90222
FDC-50G	1/2"	6.063	3.000	2.875	1	5	293	90212
FDC-75G	3/4"	6.063	3.000	2.875	1	5	305	97214
FDC-100G	1"	6.063	3.000	2.875	1	5	313	97216