

MALLEABLE IRON/HOT DIPPED GALVANIZED INSULATED BUSHINGS

FOR THREADED RIGID CONDUIT AND IMC



APPLICATION:

- Used with a locknut to terminate threaded/threadless rigid and IMC conduit to a box or enclosure and to provide a smooth pulling surface. Thermoplastic liner prevents damage to wire insulation. Liner rated at 150°C.

FEATURES:

- The plastic liner won't chip, crack, swell or shrink. It resists corrosion, chemicals and temperature extremes.

STANDARD MATERIALS:

Malleable Iron

STANDARD FINISH:

Hot Dipped Galvanized/Zinc plated





OPTIONAL FINISH:

Remove the "G" for Zinc plated
See page 88.

CERTIFICATIONS AND COMPLIANCES



UL LISTED E198258
UL Standard: UL514B
NEMA FB-1
ASTM Rated



TYPE 1206G

For Threaded Rigid Conduit and IMC

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	UNIT PACK	MASTER PACK	LBS./100 PCS	UPC#
1206G	1/2"	1.19	0.50	100	1000	6	12063
1207G	3/4"	1.44	0.56	100	500	10	12073
1208G	1"	1.75	0.63	50	500	15	12083
1209G	1-1/4"	2.13	0.75	25	250	20	12093
1210G	1-1/2"	2.13	0.88	25	250	25	12103
1211G	2"	2.81	0.94	—	25	30	12113
1212G	2-1/2"	3.38	1.00	—	25	55	12123
1213G	3"	4.06	1.13	—	25	66	12133
1214G	3-1/2"	4.50	1.19	—	25	72	12143
1215G	4"	5.19	1.31	—	25	103	12153
1216G	5"	6.06	1.31	—	10	147	12163
1217G	6"	7.15	1.31	—	10	184	12173

Also available with lay-in lugs.